

SAFETY DATA SHEET

Section 1 - Identification of The Material and Supplier

KIS – Klenall Industrial suppliers	Phone: 02 4723 9600 (office hours)
4 Cassola Place,	Email: sales@mykis.com.au
Penrith, NSW 2750	

Chemical nature:	Blend of solvents; principally butyl icinol.
Trade Name:	KIS-C11 Graffiti Remover
Product Use:	Texta, graffiti, pen and ink remover.
Creation Date:	July, 2005
This version issued:	November, 2020 and is valid for 5 years from this date.
Poisons Information Centre: Phone 13 1126 from anywhere in Australia	

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Hazardous according to the criteria of SWA Australia.

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

Risk Phrases: R10, R43, R65, R20/21/22, R36/37/38. Flammable. May cause sensitisation by skin contact. Harmful: May cause lung damage if swallowed. Harmful by inhalation, in contact with skin, and if swallowed. Irritating to eyes, respiratory system and skin.

Safety Phrases: S16, S20, S23, S28, S37, S38, S46, S60, S61, S62, S1/2, S24/25. Keep away from sources of ignition - No smoking. When using, do not eat or drink. Do not breathe vapours, mists or spray. After contact with skin, wash immediately with plenty of soap and water. Wear suitable gloves. In case of insufficient ventilation, wear suitable respiratory equipment. If swallowed, contact a doctor or Poisons Information Centre immediately and show this container or label. This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Refer to special instructions/Safety Data Sheets. If swallowed, do not induce vomiting: seek medical advice immediately and show this SDS. Keep locked up and out of reach of children. Avoid contact with skin and eyes.

SUSMP Classification: S6

ADG Classification: Class 3: Flammable liquids. **UN Number:** 1993, FLAMMABLE LIQUID, N.O.S.



GHS Signal word: DANGER.

HAZARD STATEMENT:

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

- H312: Harmful in contact with skin.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H320: Causes eye irritation.
- H332: Harmful if inhaled.
- H335: May cause respiratory irritation.

PREVENTION

- P102: Keep out of reach of children.
- P210: Keep away from heat, sparks, open flames and hot surfaces. No smoking.
- P233: Keep container tightly closed.
- P261: Avoid breathing fumes, mists, vapours or spray.

SAFETY DATA SHEET

Issued by: aiMix Chemicals Pty Ltd

Phone: 02 9623 3288 (office hours)

P262: Do not get in eyes, on skin, or on clothing. P264: Wash contacted areas thoroughly after handling.

SAFETY DATA SHEET

Issued by: aiMix Chemicals Pty Ltd Phone: 02 9623 3288 (office hours) Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand) P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P362: Take off contaminated clothing and wash before reuse.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313: If skin irritation or rash occurs: Get medical advice.

P337+P313: If eye irritation persists: Get medical advice.

P370+P378: In case of fire, note the following. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used. Try to contain spills, minimise spillage entering drains or water courses.

STORAGE

P405: Store locked up.

P402+P404: Store in a dry place. Store in a closed container.

P403+P235: Store in a well-ventilated place. Keep cool.

DISPOSAL

P501: If no in-house recycle or reclaim resources are suitable for this product, contact a specialist waste disposal company (see Section 13 of this SDS).

Emergency Overview

Physical Description & Colour: Clear, colourless liquid.

Odour: Mild, characteristic odour.

Major Health Hazards: 2-butoxyethanol is a severe eye irritant. Results of skin irritation studies are conflicting; however, it is considered to be a mild to moderate skin irritant in test animals. Contact dermatitis has been reported in a few cases. It is well absorbed via the inhalational, oral and dermal routes. Product is harmful by inhalation, in contact with skin, and if swallowed, irritating to eyes, respiratory system and skin, possible skin sensitiser, if aspirated, may cause lung damage.

Potential Health Effects

Note: sensitisation to ingredients such as d-limonene occurs in only a small percentage of persons, but those who are sensitised may show severe reactions. Most people may use this product without sensitisation reactions, however those sensitised to d-limonene should avoid contact with this product.

Inhalation

Short Term Exposure: Significant inhalation exposure is considered to be unlikely. Available data shows that this product is harmful, but symptoms are not available. In addition product is an inhalation irritant. Symptoms may include headache, irritation of nose and throat and increased secretion of mucous in the nose and throat. Other symptoms may also become evident, but they should disappear after exposure has ceased.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Available data shows that this product is harmful, but symptoms are not available. In addition product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: Exposure via eyes is considered to be unlikely. This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. Because of the low viscosity of this product, it may directly enter the lungs if swallowed, or if subsequently vomited. Once in the lungs, it is very difficult to remove and can cause severe injury or death. However, this product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

SAFETY DATA SHEET

Issued by: aiMix Chemicals Pty Ltd

Phone: 02 9623 3288 (office hours)

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: No significant ingredient is classified as carcinogenic by IARC.

Section 3 - Composition/Information on Ingredients				
Ingredients	CAS No	Conc,%	TWA (mg/m ³)	STEL (mg/m ³)
2-Butoxyethanol	111-76-2	50	121	not set
Liquid hydrocarbon	various	35	not set	not set
d-limonene	5989-27-5	5	not set	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

....

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: If symptoms of poisoning become evident, contact a Poisons Information Centre, or call a doctor at once. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. DO NOT allow victim to move about unnecessarily. Symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

Skin Contact: Quickly and gently blot away excess liquid. Wash gently and thoroughly with warm water (use nonabrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 20 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: This product is classified as flammable. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures. **Extinguishing Media:** Try to contain spills, minimise spillage entering drains or water courses.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

Flash point:	Not established, but known to be flammable.
Upper Flammability Limit:	No data.
Lower Flammability Limit:	No data.
Autoignition temperature:	No data.
Flammability Class:	Flammable

SAFETY DATA SHEET

Issued by: aiMix Chemicals Pty Ltd Phone: 02 9623 3288 (office hours) Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Wear full protective clothing including eve/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC. Eye/face protective equipment should comprise as a minimum, protective glasses and, preferably, goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. It should be fitted with a type A cartridge, suitable for organic vapours.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Avoid using sawdust or other combustible material. Any electrical equipment should be non-sparking. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 10,000kg or L of Dangerous Goods of Packaging Group III, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eve Protection: AS1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZS2210.

SWA Exposure Limits	TWA (mg/m³)
2-Butoxyethanol	121

STEL	(mg/m³)
not	set

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems. Ventilation: No special ventilation requirements are normally necessary for this product. However make sure that the work environment remains clean and that vapours and mists are minimised.

Eye Protection: Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

Skin Protection: If you believe you may have a sensitisation to this product or any of its declared ingredients, you should prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, PVC.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Eyebaths or eyewash stations and safety deluge showers should be provided near to where this product is being used.

Section 9 - Physical and Chemical Properties:

Physical Description & colour: Clear, colourless liquid. Odour:

Mild, characteristic odour.

SAFETY DATA SHEET

Issued by: aiMix Chemicals Pty Ltd

Phone: 02 9623 3288 (office hours)

Boiling Point:	Not available.
Freezing/Melting Point:	No specific data. Liquid at normal temperatures.
Volatiles:	Partly volatile at 100°C, but completely volatile at higher temperatures.
Vapour Pressure:	No data.
Vapour Density:	No data.
Specific Gravity:	Approx 0.9 at 20°C
Water Solubility:	Dispersible.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water Distribution	No data
Autoignition temp:	No data.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep away from sources of sparks or ignition. Handle and open containers carefully. Any electrical equipment in the area of this product should be flame proofed.

Incompatibilities: oxidising agents.

Fire Decomposition: Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Toxicity: 2-butoxyethanol is a severe eye irritant. Results of skin irritation studies are conflicting; however, it is considered to be a mild to moderate skin irritant in test animals. Contact dermatitis has been reported in a few cases. It is well absorbed via the inhalational, oral and dermal routes. Absorption studies in various species, including humans, have shown that 2-butoxyethanol is rapidly absorbed through the skin, including absorption from aqueous solutions. The respiratory uptake in volunteers in inhalational studies was approximately 57-78% of the inspired amount. Human studies indicate that dermal absorption of vapour is approximately 20% of the total vapour uptake. Following absorption, it is widely distributed throughout the body. The ingestion of large quantities of 2-butoxyethanol may result in coma, metabolic acidosis, shock and respiratory distress.

Section 12 - Ecological Information

Biodegradation studies indicate that 2-butoxyethanol will be readily degraded by micro-organisms present at sewage treatment plants. Ready biodegradability tests showed that it achieved a biodegradation rate of greater than 77% after 3 days and 100% after 7 days. A 20-day biochemical oxygen demand test and an OECD 28-day closed bottle test gave it degradation rates of 75% and 88% respectively. Literature data confirm these results.

Section 13 - Disposal Considerations

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by some means. If neither of these options is suitable in-house, contact a specialist waste disposal company.

Section 14 - Transport Information

UN Number: 1993, FLAMMABLE LIQUID, N.O.S. Hazchem Code: •3Y Special Provisions: 223, 274 Limited quantities: ADG 7 specifies a Limited Quantity value of 5 L for this class of product. Dangerous Goods Class: Class 3, Flammable liquids. Packaging Group: III Packaging Method: P001, IBC03, LP01

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6

SAFETY DATA SHEET Issued by: aiMix Chemicals Pty Ltd

Phone: 02 9623 3288 (office hours)

Product Name: KIS-C11 Graffiti Remover Page: 6 of 6 This revision issued: November, 2020

(Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, except where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this product are compliant with NICNAS regulations. The following ingredients: 2-Butoxyethanol, Liquid hydrocarbon, are mentioned in the SUSMP.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:	
ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail, 7th Edition
AICS	Australian Inventory of Chemical Substances
CAS Number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
SWA	Safe Work Australia, formerly ASCC and NOHSC
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons
UN Number	United Nations Number
THIS SDS SUMMARISES OL	JR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (December 2011)

Copyright © Kilford & Kilford Pty Ltd, February, 2019.

http://www.kilford.com.au/ Phone (02)9251 4532